


**AUTHORISED ITEMS for WATER RETICULATION SYSTEMS**

SA Water Product Description

**Valve - Resilient Seat  
 Gate Valve Double Flanged  
 (Manually Operated Valve to AS2638 Part 2  
 Square drive and clockwise closing)**



**For Buried Applications**

Alternative Description  
*Sluice Valve - Flanged*  
*Stop Valve - Flanged*

| Nom. Size<br>DN (Pressure)         | SA Water<br>Stock No.<br>(1.6 MPa) | AVK<br>(Iplex)<br>Series 57/40<br>(1.6 MPa) | Pentair<br>(1.6 MPa) | Karon<br>(Challenger)<br>(1.6MPa) | AVK (Iplex)<br>PN25<br>(2.5 MPa)<br>Series 57/80<br>Table "F"<br>Flanges | AAP Industries<br>Pty Ltd<br>(Maxiflo) |
|------------------------------------|------------------------------------|---|----------------------|-----------------------------------|--|--|
|                                    |                                    |   |                      |                                   | <b>Interim<br/>Authorisation</b>   | <b>Interim<br/>Authorisation</b>       |
| 50 (1.6 MPa)                       |                                    | *   |                      |                                   |  |  |
| 65 (1.6 MPa)                       |                                    | *   |                      |                                   |  |  |
| 80 (1.6 MPa)                       | 4820-2001                          | *   | *                    | *                                 | *  | *                                      |
| 100 (1.6 MPa)                      | 4820-2002                          | *   | Auslite              | *                                 | *  | *                                      |
| 150 (1.6 MPa)                      | 4820-2003                          | *   | Auslite              | *                                 | *  | *                                      |
| 200 (1.6 MPa)                      | 4820-2004                          | *   | *                    | *                                 | *  | *                                      |
| 225 (1.6 MPa)                      | 4820-2005                          | *   | *                    | *                                 | *  | *                                      |
| 250 (1.6 MPa)                      | 4820-2006                          | *   | *                    | *                                 | *  | *                                      |
| 300 (1.6 MPa)                      | 4820-2007                          | *   | *                    | *                                 | *  | *                                      |
| 375 (1.6 MPa)                      | 4820-3001                          | *   | *                    | *                                 | *  | *                                      |
| 400 (1.6 MPa)                      | 4820-3002                          | *   |                      | *                                 |  |  |
|                                    |                                    | <b>Series 55</b>                            |                      |                                   |  |  |
| 450 (1.6 MPa)                      | 4820-3003                          | *   | *                    |                                   |  |  |
| 450 Gear Operated                  | 4820-3004                          | *   | *                    |                                   |  |  |
| 500 (1.6 MPa)                      | 4820-3005                          | *#  | *                    |                                   |  |  |
| 500 Gear Operated                  | 4820-3006                          | *   | *                    |                                   |  |  |
| Larger sizes Available (to DN600)# |                                    | *   | *                    |                                   |  |  |

Highlighted items are included in SA Water's Valve Contract PC1111

# Also available with inbuilt bypass configuration in sizes DN450 – DN600 (Series 55/30)

**AUTHORISED ITEMS for WATER RETICULATION SYSTEMS**


SA Water Product Description

***Valve - Resilient Seat  
 Gate Valve Double Socket  
 (Manually Operated to AS2638 Part 2-  
 Pressure Rating 1.6 MPa)***

**For Buried, Restrained Joint applications ONLY**

Alternative Description

***Stop Valve –Resilient Seated - Socketed***



| Size<br>DN Pipe | SA Water<br>Stock No. | AVK<br>(Iplex) # | Pentair<br>Water | AAP Industries Pty Ltd<br>(Maxiflo)<br>Interim Authorisation |
|-----------------|-----------------------|------------------|------------------|--|
| 100 (1.6 MPa)   | 4820-0196             | *                | Auslite Φ        | *  |
| 150 (1.6 MPa)   | 4820-0200             | *                | Auslite Φ        | *  |
| 200 (1.6 MPa)   | 4820-0755             | *                | *                | *  |

# Series 2 (CI OD Equivalent) and Series 1 (ISO equivalent) available

Φ Auslite Valves are available with “Anchor Legs” for valve restraint. Legs purchased separately.


SA Water Product Description

***Fire Hydrant - Fireplug  
 Fire Hydrant - Below Ground***

Alternative Description

***Fireplug (flanged)***

***Fireplug – Air valve***



| Nom. Size<br>DN | SA Water<br>Stock No. | AVK<br>(Iplex) | Pentair<br>Water | The Poly<br>People |
|-----------------|-----------------------|----------------|------------------|--------------------|
| 80mm (1.6 MPa)  | 4210-0031             | *              | *                | *                  |
| 80mm (3.5 MPa)  | 4210-0032             |                | *                |                    |

Highlighted items are included in SA Water’s Valve Contract PC1111